YDSTECH®

>>Datasheet<<

ECS-S351

Overall Specifications

Technical Information	
processor	Intel ®Core ™ i3-6100U 2.3GHz 15W Intel ®Core ™ i5-6200U 2.3GHz 15W Intel ®Core ™ i7-6500U 2.5GHz 15W Intel ®Core ™ i3-7020U 2.3GHz 15W Intel ®Core ™ i3-7100U 2.4GHz 15W Intel ®Core ™ i5-7200U 2.5GHz 15W Intel ®Core ™ i7-7500U 2.7GHz 15W
Memory	Onboard 4GB/8GB/16GB DDR4 memory (1.2V), frequency 1333/1600/1866/2133MHz
Graphics processing	Supports one VGA port with a maximum resolution of 1920x1080 @60Hz Supports one HDMI port with a maximum resolution of 1920 x 1080 @ 60Hz.
Network card	Supports two Intel 10/100/1000Mbit Ethernet ports (Intel I21 9V and I211AT/I210AT).
storage	1 mSATA, 2 SATA 3.0, 1 MPCIE
USB	Supports 4 USB 3.0 ports and 4 USB 2.0 ports.
serial port	4 RS232 (3-wire), 2 RS232 (3-wire) / RS422 / RS485
IO	Supports 8 GPIOs and 1 SIM card slot (expandable, optional).
sound card	ALC662 High-Fidelity Sound Card (Line-Out , MIC-in)
power supply	+ 12V to + 24V voltage , + 12V is recommended. Power on (default) , trigger power on (optional) .
adapter	60W or above
temperature	Operating temperature: -20° C to + 60 ° C (optional: -40° C to + 75 ° C)
size	205 mm (length) x 140 mm (width) x 55 mm (height) (Overall dimensions excluding wall mount and external interface)
Heat dissipation	Fanless design
operating system	WIN7, WIN10 WIN11, Linux
weight	1.46 kg (bare machine) , 2.55 kg (including packaging)
color	The entire unit is blue , with black front and rear panels.